Included in package:



1 Fabrication Dummy

EN | Instructions for Use

DE | Gebrauchsanweisung

FR | Notice d'utilisation

ES | Instrucciones para el uso

IT | Istruzioni per l'uso

NO | Bruksanvisning

DA | Brugsanvisning

SV | Bruksanvisning

ΕL | Οδηγίες Χρήσης

FI | Käyttöohjeet

NL | Gebruiksaanwijzing

PT | Instruções de Utilização

PL | Instrukcja użytkowania

CS | Návod k použití

TR | Kullanım Talimatları

RU | Инструкция по использованию

JA | 取扱説明書

ZH | 中文说明书

KO | 사용 설명서



www.coyote.us/instructions-accessories



Manufactured by Coyote® 419 N. Curtis Rd., Boise, Idaho 83706 (208) 429-0026 | www.coyote.us



Coyote

CD103FD

Fabrication Dummy

For CD103 Air-Lock or CD117 Easy Off Lock CD103D Deep Air-Lock or CD117D Easy Off Deep lock



2-Year warranty against manufacturer defects, excessive wear or breakage

Made in U.S.A.

External Prosthetic Components



(
MD

EC REP

? btcl_Jok grcb
Rmucp@sqdjcqqAcIrpc
OIbDjp*RmucpQpccr
Qu_r_p*@IP2./1
K_jr_

Included in package:



1 Fabrication Dummy

EN | Instructions for Use

DE | Gebrauchsanweisung

FR | Notice d'utilisation

ES | Instrucciones para el uso

IT | Istruzioni per l'uso

NO | Bruksanvisning

DA | Brugsanvisning

SV | Bruksanvisning EL | Οδηγίες Χρήσης

FI | Käyttöohjeet

NL | Gebruiksaanwijzing

PT | Instruções de Utilização

PL | Instrukcja użytkowania

CS | Návod k použití

TR | Kullanım Talimatları

RU | Инструкция по использованию

JA | 取扱説明書

ZH | 中文说明书

KO | 사용 설명서



www.coyote.us/instructions-accessories



Manufactured by Coyote® 419 N. Curtis Rd., Boise, Idaho 83706 (208) 429-0026 | www.coyote.us





For GD103 Air-Lock or GD117 Easy Off Lock GD103D Deep Air-Lock or GD117D Easy Off Deep lock



2-Year warranty against manufacturer defects, excessive wear or breakage

Made in U.S.A.

External Prosthetic Components





? btcl_Jgk grcb Rmucp@sqglcqq Aclrpc 01 b Djp*Rmucp Qpccr Qu_r_p*@IP 2./1 K_jr_

Flexible Inner Socket with Coyote Designs Fabrication Dummy CD103FD



1. Put CD103FD fabrication dummy over anchor.



2. Pull preferred flexible plastic over socket and installed fabrication dummy using a vacuum system.



 Pressing in around fabrication dummy will help remove any air pockets.



 If needed use parachute cord or rope to pull plastic tight to dummies edge.



5. Let plastic cool before cutting fabrication dummy free.



6. Cut tooling free with cast saw, knife or utility knife.



7. Remove tooling from anchor.







9. Pull a PVA bag over the an-

8. Sand flexible inner down so anchor is almost 100% exposed

Pull a PVA bag over the anchor and cast. Glue your lock to anchor and start laminating.

Flexible Inner Socket with Coyote Designs Fabrication Dummy CD103FD



1. Put CD103FD fabrication dummy over anchor.



2. Pull preferred flexible plastic over socket and installed fabrication dummy using a vacuum system.



3. Pressing in around fabrication dummy will help remove any air pockets.



 If needed use parachute cord or rope to pull plastic tight to dummies edge.



Let plastic cool before cutting fabrication dummy free.



6. Cut tooling free with cast saw, knife or utility knife.



7. Remove tooling from anchor.





WIN CONTRACTOR OF THE PARTY OF

Pull a PVA bag over the anchor and cast. Glue your lock to anchor and start laminating.

8. Sand flexible inner down so anchor is almost 100% exposed