





1 With liner on patient position band in desired location.



Tape off both ends of 6 the band.



Smooth the silicone out 11 with a tongue depressor. Make sure to saturate the material.



2 Mark band location on distal and proximal sides of band.



Remove the band



Check the edges for 12 areas that need more silicone adhesive.



3



Add extra tape to 8 protect a wider area.



13 Smooth the silicone out.



For unconventional band 4 position mark band in multiple locations.






Carefully place the seal 14 band over the glued area.



Wrap the liner with 5 electrical tape or vinyl tape next to the band without overlapping it.



10 Put a bead of silicone adhesive around the liner about the thickness of a pencil.



Center the band with 15 tape to the edges.




16 Push the air bubbles out from under the band




17 Remove the tape from the liner.



18 Create a seal band edge with silicone adhesive.




19 Roll tape next to band edge approximately 1/4 inch space from band.



20 Smooth silicone into fabric and band. Making a sealed edge.



21 Remove tape.



22 Check your work and let the silicone set up for at least two hours before putting it on patient.

Wave Suction Band sizes				
Part Number	Size	Circumference	Width	Thickness
CD130BS	Small	16cm - 25cm	7.62cm	4mm
CD130BM	Medium	25cm - 37cm	7.62cm	4mm
CD130BL	Large	37cm - 49cm	7.62cm	4mm
CD130BX	Extra Large	49cm - 64cm	7.62cm	4mm
CD130BXX	Extra Extra Large	64cm - 77cm	7.62cm	4mm

Lay-up instructions are helpful hints on how to work with the lock and connector. Actual lay-ups are responsibility of the technician and/or practitioner.