



# CD207M

## Medium Flex Kit

Resilergy™ Dynamic Strut AFO

Weight Range 125-225 lbs.

Light to Medium Activity Level



6-month warranty against manufacturer defects, excessive wear or breakage.

External Prosthetic Components



[www.coyote.us/instructions](http://www.coyote.us/instructions)



8 11576 02396 2

CD207M.post.revA.11082022



EC REP

Manufactured by Coyote®  
419 N. Curtis Rd., Boise, Idaho 83706 USA  
(208) 429-0026 | [www.coyote.us](http://www.coyote.us)



Advena Limited  
Tower Business Centre  
2nd Flr, Tower Street  
Swatar, BKR 4013  
Malta

## Parts Included



A. Strut (1) (10.5 x 1.5)

B. Screws (4)

(2) - 6x18 for Top Mounting Plate

(2) - 6x20 for Bottom Mounting Plate

C. Black Screws 6x14 (4)

D. Clamp Washer (4)

E. AFO Mounting Plate (2)

(1) Upper Mounting Plate - Short Posts

(1) Lower Mounting Plate - Tall Posts

F. AFO Fab Tooling Pieces (2)

G. AFO Plate Foam (2)

EN | Instructions for Use  
DE | Gebrauchsanweisung  
FR | Notice d'utilisation  
ES | Instrucciones para el uso  
IT | Istruzioni per l'uso  
NO | Bruksanvisning  
DA | Brugsanvisning  
SV | Bruksanvisning  
EL | Οδηγίες Χρήσης  
FI | Käyttöohjeet

NL | Gebruiksaanwijzing  
PT | Instruções de Utilização  
PL | Instrukcja użytkowania  
CS | Návod k použití  
TR | Kullanım Talimatları  
RU | Инструкция по использованию  
JA | 取扱説明書  
ZH | 中文说明书  
KO | 사용 설명서



<https://www.coyote.us/instructions-dynamicstrut>